

coharo coatings **CLEAR COAT**



PRODUCT OVERVIEW

Coharo Coatings Clear Coat is a clear acrylic silicone hybrid sealer that creates a subtle glow when applied to Coharo Coatings finishes. It provides added protection and durability, creating a washable surface.

Clear Coat can be used over all the Coharo Coatings range to enhance and protect from weathering, wear and tear and water ingress.

Clear Coat is water based and is sprayed on and back rolled in a 2 coat application. It dries to an attractive satin finish.

FEATURES AND BENEFITS

- Ready to use – spray and back roll
- Excellent water repellency
- Satin finish
- Increases durability and longevity of the coating
- Creates a washable surface
- Easy to use

SPECIFICATIONS

TYPICAL SYSTEMS	Coharo Coatings Clear Coat is designed for use over any suitable surface which has been prepared correctly following Casafico's application procedures*
PREPARATION	Substrate must be clean, sound and free of all powdery residues, oils and release agents. Any crumbling, loose or damaged material must be removed. Pre-painted surfaces must have all loose material removed with a wire brush.
MIXING	Stir prior to use
APPLICATION PROCEDURE & EQUIPMENT	<ul style="list-style-type: none"> ● Stir well and spray the back roll with a 5mm nap roller ● Ensure there are no drip marks before allowing to dry, once 50% dry, second coat must be applied
CURING TIME	Protect from frosts or rain for the first 8 hours. Allow 2 days for full cure.
COVERAGE PER PAIL	75m ² per litre depending on substrate porosity / 2 coats

SPECIFICATIONS

PACKAGING	Clear Coat is supplied in 15 litre pails
CLEAN UP	Clean up with water before it dries
STORAGE & SHELF LIFE	12 months shelf life in original/unsealed container

PRECAUTIONS AND LIMITATIONS

- Silicone or oil contaminated surfaces are not suitable for sealing
- Not designed for application to sealed or glazed surfaces (Glazed Bricks, Tiles, Glass etc)
- Protect from frosts or rain for the first 8 hours
- Do not apply below 5°C or above 30°C
- Users must make their own determination as to the suitability of this product relevant to requirement

**Control joints are ultimately the builders responsibility.*

The information contained in this document is based on information available at the time of writing which we believe is accurate and reliable. Casafico Pty Ltd reserves the right to change the information without prior notice.

For all Casafico products technical assistance call 1300 COHARO