

coharo coatings **LONDON FINISH**



PRODUCT OVERVIEW

Coharo Coatings London Finish is a glossy decorative coating used to achieve a polished plaster finish, creating unique depth and the appearance of movement through soft, polished layers.

London Finish can be tinted to any colour. It is applied using a stainless trowel and polished until reflective. Apply onto a flat, properly prepared surface and create bespoke effects with various artistic trowel techniques.

Coharo Coatings London Finish formulation is tactile and refined, developed for ease of use, high adhesion and water resistance properties. It is suitable for wet areas once sealed with Coharo Coatings Marble Finish Clear then Lustró Wax.

FEATURES AND BENEFITS

- Pre-blended - just add water
- Excellent crack resistance
- Exceptional workability
- Polishes to a reflective “glass” finish
- High adhesion and water resistance properties
- Suitable for wet areas such as bathrooms and kitchens
- Can be coloured to any colour

SPECIFICATIONS

<p>TYPICAL SYSTEMS</p>	<p>Coharo Coatings London Finish is designed for use in 0.1 -0.5mm thick application layers over any suitable surface which has been prepared correctly following Casafico’s Coharo Systems Guide.*</p> <p>London Finish is suitable for wet areas as an alternative to tiles. London Finish complies with AS3740 when the correct lining board and waterproofing requirements are met.</p>
<p>PREPARATION</p>	<p>Substrate must be clean, sound and free of all powdery residues, oils and release agents. Any crumbling, loose or damaged material must be removed. Pre-painted surfaces must have all loose material removed with a wire brush.</p> <p>Coharo Coatings base preparation products must be used in accordance with our recommendations. Then the substrate must be clean and dry/ cured before applying London Finish.</p>

SPECIFICATIONS	
MIXING	<p>Add approximately 4L of water to a 15L pail and pour pail contents in to the bucket, depending on consistency desired. Mix using a high speed drill with a suitable shearing blade. Mix until lump free.</p> <ul style="list-style-type: none"> • Addition of 500mL of Lustro Wax when mixing can improve the products performance.
APPLICATION PROCEDURE & EQUIPMENT	<ul style="list-style-type: none"> • Apply using a trowel onto prepared substrate (Coharo Coatings Smooth Coat or Patch/adhesive is recommended as a base coat. For full specification see Systems Guide). • Leave to stabilise on the wall and finish with a clean marble polishing trowel. Different trowel techniques can create various finish patterns. Do not use water. • Care should be taken in preparation of the area; areas not to be coated should be carefully masked and protected as material can be difficult to remove if allowed to fully dry.
CURING TIME	<p>London Finish will set in 1 hour depending on temperature and substrate. London Finish can be recoated as soon as stabilised if necessary to achieve your desired look. (When you put your hand on the wall and not leave any prints).</p>
COVERAGE PER PAIL	<p>Approximately 40m² per 15L pail depending on thickness</p>
PACKAGING	<p>London Finish is supplied in 15 litre/ 10kg pails (powder)</p>
CLEAN UP	<p>Clean up with water before it dries</p>
STORAGE & SHELF LIFE	<p>12 months shelf life in original/unsealed container</p>

PRECAUTIONS AND LIMITATIONS

- Silicone or oil contaminated surfaces are not suitable for rendering
- Not designed for application to sealed or glazed surfaces (Glazed Bricks, Tiles, Glass etc)
- Not to be applied greater than .5mm thick
- Protect from frosts or rain for the first 8 hours
- Do not apply below 5°C or above 30°C
- *The provision of expansion joints at 'weak spots' ie:
 - Above and below openings
 - At all level changes
 - At the junction of different substrates
 - As specified by the project engineer
- Users must make their own determination as to the suitability of this product relevant to requirement

**Control joints are ultimately the builders responsibility.*

The information contained in this document is based on information available at the time of writing which we believe is accurate and reliable. Casafico Pty Ltd reserves the right to change the information without prior notice.

For all Casafico products technical assistance call 1300 COHARO