

# *coharo* coatings

## **WET TEXTURE**



### **PRODUCT OVERVIEW**

Coharo Coatings Wet Texture is a pre-mixed, acrylic texture made from 100% recycled glass aggregate. Wet Texture is highly crack resistant and offers flexibility and convenience – simply trowel and float.

Available in a medium-coarse grain finish, Wet Texture is ideal for overcoating properly prepared surfaces, such as Coharo Coatings Levelling Coat, Smooth Coat or Patch Adhesive.

Wet Texture is applied with a steel trowel and floated with a plastic float and can be overcoated with 2 coats of external paint to give a durable, weather resistant finish.  
Tintable to any colour.

### **FEATURES AND BENEFITS**

- Made from 100% recycled glass aggregate
- Ready to apply
- Excellent crack resistance
- Very high water resistance
- Washable once cured
- Easy to use
- Attractive texture finish
- Tintable to any colour

### **SPECIFICATIONS**

<b>TYPICAL SYSTEMS</b>	Coharo Coatings Wet Texture is designed for use in 1mm applications over any suitable surface which has been prepared correctly following Casafico's application procedures*
<b>PREPARATION</b>	Substrate must be clean, sound and free of all powdery residues, oils and release agents. Any crumbling, loose or damaged material must be removed. Pre-painted surfaces must have all loose material removed with a wire brush.
<b>MIXING</b>	Stir prior to use
<b>APPLICATION PROCEDURE &amp; EQUIPMENT</b>	<ul style="list-style-type: none"> <li>● Apply using a trowel onto prepared substrate, we recommend Coharo Coatings Levelling Coat, Smooth Coat or Patch Adhesive.</li> <li>● Once applied, Wet Texture can be floated to achieve a textured finish.</li> <li>● Care should be taken in preparation of the area; areas not to be coated should be carefully masked and protected as material can be difficult to remove if allowed to fully dry.</li> </ul>

## SPECIFICATIONS

<b>CURING TIME</b>	Wet Texture will set in 1 – 4 hours depending on substrate moisture and thickness applied. Allow 48 hours before recoating.
<b>COVERAGE PER PAIL</b>	10m <sup>2</sup> per pail
<b>PACKAGING</b>	Wet Texture is supplied 15 Litre pails with 48 pails to a pallet
<b>CLEAN UP</b>	Clean up with water before it dries
<b>STORAGE &amp; SHELF LIFE</b>	12 months shelf life if stored in original unsealed contained away from sunlight

## PRECAUTIONS AND LIMITATIONS

- Silicone or oil contaminated surfaces are not suitable for rendering
- Not designed for application to sealed or glazed surfaces (Glazed Bricks, Tiles, Glass etc)
- Protect from frosts or rain for the first 24 hours
- Do not apply below 5°C or above 30°C
- \*The provision of expansion joints at 'weak spots' ie:
  - Above and below openings
  - At all level changes
  - At the junction of different substrates
  - As specified by the project engineer
- Users must make their own determination as to the suitability of this product relevant to requirement

*\*Control joints are ultimately the builders responsibility.*

*The information contained in this document is based on information available at the time of writing which we believe is accurate and reliable. Casafico Pty Ltd reserves the right to change the information without prior notice.*

**For all Casafico products technical assistance call 1300 COHARO**